# **Product information**

# Diesel Purge



#### **Description**

Diesel Purge contains a mixture of agents with powerful cleaning properties. The special additives guarantee corrosion protection and increase ignition performance (cetane number).

### **Properties**

- boosts the cetane number

- increases operational reliability

- eliminates diesel knocking

- reduces deposits

- cleans the fuel system

- good corrosion protection

- quarantees optimum combustion

- highly economical

#### **Technical data**

Base Additive gelöst in

Trägerflüssigkeit / additives dissolved in

carrier fluid

Density at 20 °C 0,82 g/cm<sup>3</sup>

Color / appearance hellbraun, klar / light

brown, clear

Flash point 63 °C

Regulation on Flammable A III

Liquids Class (Germany)

Pour point -35 °C

Odor charakteristisch /

characteristic

Form flüssig / liquid

Viscosity at 40 °C <7 mm²/s

### Areas of application

Used for all diesel engines to prevent and eliminate problems associated with uneven idling and partial-load knocking. Quantity to be used for preventive and remedial use: 500 ml.

#### **Application**

Preventive use

Add to diesel fuel according to the inspection intervals

#### Remedial use

Unclip the fuel pipe and immerse the end in the Diesel Flush. Close the fuel return pipe or feed that into the Diesel Flush. Start the engine and allow the engine to run at different speeds with the Diesel Flush unmixed. After the cleaning process, assemble the vehicle's system. In extreme cases, repeat the clean-

ing procedure if necessary.

## Available pack sizes

500 ml Can sheet metal 5170 D-F-NL

2101

500 ml Can sheet metal 2186

D-H-R0

500 ml Can sheet metal 2509

D-E-P

500 ml Can sheet metal 2813

DK/N-S-FIN

500 ml Can sheet metal 1811

GB-GR-I

500 ml Can sheet metal

8380 GB-ARAB-F

500 ml Can sheet metal 2666

D-PL-BG

500 ml Can sheet metal 1912

1912 D-RUS-UA

500 ml Can sheet metal

2790

\_\_\_\_\_

GB-AUS 20809

500 ml Can sheet metal

D-GB-SLO-SRB-HR

1 l Can sheet metal

D-GB-I-E-P

5 l Canister plastic

2525 D-GB-I-E-P

50 l Drum sheet metal

2524

oo t Brain sheet metat

D-GB

205 l Drum sheet metal

2528 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-13 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de